



MAXIMUM®

FIANDRE EXTRALITE



New Delhi | Kishangarh (Raj.) | Ahmedabad

Regd. Office :  
Khasra no. 1067, 1068,  
1072 & 1073, Village - Asola,  
New Delhi - 110074  
M : +91 99587 91101  
✉ : [aclasssurfaces@gmail.com](mailto:aclasssurfaces@gmail.com)

SP-27, Phase-Vth,  
RIICO Industrial Area,  
Madanganj,  
Kishangarh - 305801 (Raj.)  
M : +91 97994 58000

68/2,  
Najafgarh Road,  
Moti Nagar,  
New Delhi- 110015  
M : +91 9999800071

Showroom : 1411,  
14th Floor, Shapath V,  
SG Highway,  
Ahmedabad - 380015  
T : +91 079 40036948

www.aiclassmarble.co.in  
f t i n g+ : [aclassmarble](https://www.aiclassmarble.co.in)



## FORMATS

### 300x150 cm & 300x100 cm

The several decades of experience, aptitude for experimenting and ability for innovation. GranitiFiandre has been able to combine ceramic tradition and technology, respect for the environment and research. These characteristics have lead Fiandre, a leader in producing high-end, fully body porcelain stoneware-to create a new material for architecture and design: Maximum, the first porcelain stoneware offers its range with new "smart" formats, such as 300x150 cm and 300x100 cm.

## THICKNESS

A new concept of creativity tailored like a second skin in 6 MM thickness.



### MAXIMUM FIANDRE EXTRALITE®

Maximum slabs, in addition to the exceptional size, offer the novelty of a minimum thickness. The technology available has made it possible to create stunning slabs in an astonishing size associated with a minimum thickness of 6 mm and surfaces without any harshness: characteristics that make it an "essential" material, despite the outstanding size for this feature.

## FINISHES



POLISHED



HONED

The Marmi Maximum materials are available with two finishes - Polished and Honed, to meet various aesthetic and application requirements. Maximum, the result of the most advanced research combining performances and aesthetics, is the first 100% porcelain stoneware material in such impressive sizes made in completely polished finish as well. This feature bestows additional value to a product already recognized as one of a kind.





**CALACATTA STATUARIO**  
Polished  
300 X 150 cm / 3 x 1.5 m



**CALACATTA LIGHT**  
Polished  
300 X 150 cm / 3 x 1.5 m



**CALACATTA ELITE**  
Polished  
300 X 150 cm / 3 x 1.5 m



**BRIGHT ONYX**  
Polished  
300 X 150 cm / 3 x 1.5 m



**GOLD ONYX**  
Polished  
300 X 150 cm / 3 x 1.5 m



**SOFT ONYX**  
Polished  
300 X 150 cm / 3 x 1.5 m



**ATLANTIC GREY**  
Polished  
300 X 150 cm / 3 x 1.5 m



**NEBULA GRIGIA**  
Polished  
300 X 150 cm / 3 x 1.5 m



**GLAM BRONZE**  
Polished  
300 X 150 cm / 3 x 1.5 m



**PIETRA GREY**  
Polished  
300 X 150 cm / 3 x 1.5 m



**NERO SUPREMO**  
Polished  
300 X 150 cm / 3 x 1.5 m





EMINENT WOOD  
MAXIMUM®



EMINENT GREY

Polished  
300 X 150 cm / 3 x 1.5 m



EMINENT BROWN

Polished  
300 X 150 cm / 3 x 1.5 m







# HQ RESIN MAXIMUM®



**WHITE RESIN**  
Honed  
300 X 100 cm / 3 x 1 m



**CINDER RESIN**  
Honed  
300 X 100 cm / 3 x 1 m



**GREY RESIN**  
Honed  
300 X 100 cm / 3 x 1 m



**DARK RESIN**  
Honed  
300 X 100 cm / 3 x 1 m





MEGALITH  
MAXIMUM®



MEGA WHITE

Honed  
300 X 100 cm / 3 x 1 m



MEGA GREY

Honed  
300 X 100 cm / 3 x 1 m



MEGA BROWN

Honed  
300 X 100 cm / 3 x 1 m



MEGA BLACK

Honed  
300 X 100 cm / 3 x 1 m





# URBAN GREAT MAXIMUM®



URBAN GREAT WHITE

Honed  
300 X 100 cm / 3 x 1 m



URBAN GREAT IVORY

Honed  
300 X 100 cm / 3 x 1 m



URBAN GREAT GREY

Honed  
300 X 100 cm / 3 x 1 m






URBAN GREAT DOVE

Honed  
300 X 100 cm / 3 x 1 m



# TECHNICAL FEATURES

Physical properties	Norms	Required standards	
 Water absorption	ISO 10545.3	≤0,5%	
 Sizes	ISO 10545.2	Length and width	±0,6% max
		Thickness	±5% max
		Linearity	±0,5% max
		Ortogonalidad	±0,6% max
		Surface Flatness	±0,5% max
 Modulus of rupture	ISO 10545.4	≥35N/mm <sup>2</sup>	
 Resistance to deep abrasion	ISO 10545.6	≤175 mm <sup>3</sup>	
 Thermal expansion coefficient	ISO 10545.8	Testing method available	
 Thermal shock resistance	ISO 10545.9	Testing method available	
 Frost resistance	ISO 10545.12	No sample must show alterations to surface	
 Chemical resistance	ISO 10545.13	No sample must show visible signs of chemical attack (acids-basis-additives for pools) except for products containing hydrofluoric acid and derivate.	
 Color resistance to light	DIN 51094	No sample must show noticeable colour change	
 Brightness (polished)			
 Skid resistance Average coefficient of friction (μ)	DIN 51130		
	BCR		
 Stain resistance	ISO 10545.14	Unglazed tiles: testing method available	
Fiandre reserves the right to modify technical and formal details included in this catalogue.		According to the EN 14411 Encl. G/ISO 13006 Encl.G for unglazed dry-pressed ceramic tiles of the group BIa.	

	MAXIMUM® FIANDRE EXTRALITE		MAXIMUM® FIANDRE EXTRALITE	
	Average value of production		Honed	Average value of production Polished
	0,08%			< 0,1%
	±0,1% ±5,0% - ±0,1% ±0,2%			±0,1% ±5,0% - ±0,1% ±0,2%
	50N/mm <sup>2</sup>			47N/mm <sup>2</sup>
	140 mm <sup>3</sup>			140 mm <sup>3</sup>
	6 MK <sup>-1</sup>			6 MK <sup>-1</sup>
	Resistant			Resistant
	Frost proof			Frost proof
	Unaffected			Unaffected
	No change in brightness or colour			No change in brightness or colour
	More or equal than natural marble and granite, polished or honed.			More or equal than natural marble and granite, polished or honed.
	R9			
	Resistant to stain	Classe 4 ÷ 5		Resistant to stain Classe 2 ÷ 3
	Dry Rubber Wet Rubber Dry Leather			

